



## **LT Series Folding Gates STANDARD CONSTRUCTION**

MAXIMUM SIZE	13 ft. wide (single gate) or 26 ft. wide (bi-parting gate), 6 ft. high (extended)
GATE BODY	Diagonal 3/4" x 3/8" x 14 gauge steel lattice channels in a diamond pattern, spaced approximately 6" apart, riveted back-to-back through zinc plated steel washers between channels, non-metallic vertical glide rollers enclosed in lead and rear bar, vertical intermediate support on single gate sections over 8 ft. wide
LEAD & REAR BARS	1 7/8" x 1 3/8" x 14 gauge formed steel box channel
GATE PIVOT	Malleable iron casting at top and bottom of rear bar
LOCKING	Hasp suitable for padlocking gate in closed position (full height lock post on single gate), 3/4" cane bolt on lead bar of bi-parting gate or intermediate support on single gate, pivoting steel tie-back arm to hold gate in open position
BOTTOM CASTER	Hard rubber 2" swivel caster on bottom of lead bar and intermediate support
FINISH	Hot-dip galvanized, or factory applied black, bronze or gray paint
WARRANTY	One year limited warranty (excluding finish)
COMMON OPTIONS	Outrigger type bottom double-casters Unequal pair bi-parting gates Portable gates Top roller (in lieu of bottom caster) Keyed pin type or cylinder locking device Gate cabinets - surface mount or recessed, shallow or deep designs Powder coat finish