


SPECIFICATIONS

MAXIMUM SIZE CURTAIN	16 ft. wide, 14 ft. high, 200 sq. ft. Interlocking 24 gauge galvanized steel Type 'C' curved slats with endlocks riveted to alternate slats, designed to withstand a 20 PSF windload
BOTTOM BAR GUIDES	T-shape aluminum extrusion with vinyl weatherstrip Formed 12 gauge steel U-channel guides and 1/8" min. steel wall angles bolted together and to wall with 3/8" fasteners 24" apart
BARREL BRACKETS	4 1/2" min. steel pipe and solid steel shaft with sealed bearing and torsion spring(s) designed for 10,000 operating cycles
HOOD	1/8" min. steel plates with sealed bearing on operator side and external tension adjustment wheel <i>NOT STANDARD</i> (24 gauge galvanized steel is available as an option)
OPERATION LOCKS	Push-up to 12 ft. wide, 10 ft. high, 96 sq. ft. or chain hoist with reduction sprockets on larger sizes Slide locks on coil side of bottom bar
FINISH	Baked-on primer and top coat on slats (and optional hood) - tan opposite coil side/off-white coil side, or grey both sides - clear anodized aluminum bottom bar, shop painted black primer on guides and brackets
WARRANTY	One year limited warranty (excluding finish)

COMMON OPTIONS



OTHER OPTIONS

- Heavier gauge slats
- Louvered slats
- Tubular bottom bar with cylinder locks
- Sloping or irregular shaped bottom bars
- Galvanized or powder coat finishes


CURTAIN & BOTTOM BAR DETAILS



GUIDE DETAILS



CLEARANCES (typical face mount door shown)



PS	CS#	AS	MS	TS
6"	7"	7"	7"	7"


#CS is 8" for chain hoist with optional cast iron gears
 'V' for doors to 15' wide, 12 ft. high is 12"
 'V' for most larger size doors is 15"

GENERAL NOTES:


Clearances are based upon standard door construction. Reduced clearances may be available. Some options may require additional clearance. Shop drawings for specific applications are available. Consult factory for any information not shown.

* Available as an option


CHAIN HOIST
 MODEL: SDFC
 (Reduction sprockets shown - cast iron gears similar)



AWNING CRANK*
 MODEL: SDFA
 (To 16' wide, 10' high 150 sq. ft.)



MOTOR OPERATOR*
 MODEL: SDFM



903 Jan Mar Court, Minneola, FL 34715
Toll Free 1(800) 357-DOOR (3667)
 www.commercialdoorsdirect.com